Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-460-9482

Body Style:	
Straight shape	
Overall Length:	
Between 1.230 inches and 1.260 inches	
Overall Height:	
Between 1.146 inches and 1.170 inches	
Overall Width:	
Between 4.297 inches and 4.330 inches	
Environmental Protection:	
Salt water resistant and moisture resistant and vibration resistant and shock resistant and therma	al shock resistant
Center To Center Distance Between Mounting Facilities Parallel To Height:	
Between 0.558 inches and 0.566 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
Between 3.871 inches and 3.879 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.615 inches and 0.630 inches	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
185 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
7.5 single mating end single contact grouping	
Polarization Method:	
Mating end	
Shell Type:	
Solid	
Connector Locking Method:	
Friction	
End Application:	
C17a acft	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping	
Terminal Type:	
Wire wrap single mating end single contact grouping	
Shell Material:	
Aluminum alloy	

NSN 5935-01-460-9482

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Cadmium and nickel Included Contact Quantity: 185 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material: Gold Shelf Life: N/a Unit Of Measure: --

No

Fiig:

A039b0