Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-460-9510

Body Style:
Straight shape
Overall Length:
Between 1.230 inches and 1.260 inches
Overall Height:
Between 1.146 inches and 1.170 inches
Overall Width:
Between 4.297 inches and 4.330 inches
Environmental Protection:
Salt water resistant and moisture resistant and vibration resistant and shock resistant and thermal shock resistant
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.558 inches and 0.566 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 3.871 inches and 3.879 inches
Distance From Mounting Shoulder To Front Face:
Between 0.615 inches and 0.630 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
48 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
End Application:
C17a acft
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:
Wire wrap single mating end single contact grouping
Shell Material:
Aluminum alloy

NSN 5935-01-460-9510

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Cadmium and nickel Included Contact Quantity: 48 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material: Gold Shelf Life: N/a Unit Of Measure: --

No

Fiig:

A039b0