

View Online at <https://aerobasegroup.com/nsn/5935-01-461-0188>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle shape, external/internal coupling

Overall Length:

0.583 inches

Overall Height:

0.583 inches

Overall Width:

0.312 inches

Environmental Protection:

Vibration resistant and shock resistant and thermal shock resistant and corrosion resistant and moisture resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Sma all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Rubber synthetic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-c-530, 1/2 h federal specification single material response all mating ends single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Material Specification:

Qq-s-764, cl 303 federal specification single material response

Insert Material Specification:

Zz-r-765 federal specification single material response all mating ends or mil-r-5847 military specification single material response all mating ends

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial pin all mating ends single contact grouping

Precious Material And Location:

E0.005 gold

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.