Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-461-2317

Thread Class:
2a
Thread Direction:
Right-hand and right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
36.0 millimeters
Overall Diameter:
Between 52.1 millimeters and 52.7 millimeters
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Distance From Mounting Shoulder To Front Face:
16.7 millimeters
Mounting Facility Thickness:
Between 1.5 millimeters and 3.2 millimeters
Threaded Device Type:
Back shell and coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
21-35 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Size:
31.0 millimeters and 1.375 inches and 38.0 millimeters
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:
Printed circuit circle meting and circle contact grouping

Printed circuit single mating end single contact grouping



Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium Shell Surface Treatment Specification: Qq-p-416 federal specification single treatment response **Thread Tolerance Class:** 6g external and 6g external **Included Contact Quantity:** 79 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Altered from 81349 d38999/24wg35sn **Precious Material And Location:** Contact surfaces gold **Precious Material:** Gold **Thread Series Designator:** Iso m and special acme and iso m Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0