Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-461-8039



### **Thread Class:**

2b

**Thread Direction:** 

Right-hand

### Body Style:

Straight shape, internal coupling w/backshell

### **Overall Length:**

2.000 inches

#### **Overall Diameter:**

1.719 inches

### **Environmental Protection:**

Vibration resistant

### **Threaded Device Type:**

Coupling facility

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

24-2 single mating end

### **Contact Removability:**

Removable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

### Contact Maximum Ac Voltage Rating In Volts:

200.0 single mating end single contact grouping

### Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

### **Polarization Method:**

Keyway or multiple keyway

### **Insert Position In Deg:**

0.0

### Shell Type:

Solid

### Connector Locking Method:

Internally threaded coupling ring

### Thread Size:

1.500 inches

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Silver single mating end single contact grouping

# NSN 5935-01-461-8039

Electrical Plug Connector - Page 2 of 2



### Insert Material:

Plastic diallyl phthalate single mating end

### **Terminal Type:**

Crimp single mating end single contact grouping

### Shell Material:

Aluminum alloy

### Shell Surface Treatment:

Cadmium and chromate

### **Included Contact Quantity:**

7 single mating end single contact grouping

### Included Contact Type:

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:** 

0.007 silver grains, troy

### **Precious Material:**

Silver

### **Test Data Document:**

71468-ca3106r24-2pf80 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: --Demilitarization:

No

Fiig:

A039b0