

View Online at <https://aerobasegroup.com/nsn/5935-01-461-8649>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling strain relief

Overall Length:

7.188 inches

Overall Height:

Between 1.238 inches and 1.278 inches

Overall Width:

Between 1.238 inches and 1.278 inches

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.968 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.968 inches

Cable Entrance Diameter:

Between 0.438 inches and 0.750 inches

Distance From Mounting Shoulder To Front Face:

Between 0.878 inches and 0.898 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

15-21 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

62.0 and 145.0 and 180.0 and 280.0

Shell Type:

Solid

Connector Cable Strain Relief Method:

Cable clamp

Thready Qty Per Inch (tpi):

10

Thread Size:

1.062 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic fluorosilicone single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and chromate and nickel

Included Contact Quantity:

21 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Thread Series Designator:

Double stub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0