## NSN 5935-01-462-7316

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-462-7316 **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 32.5 millimeters **Overall Diameter:** 44.5 millimeters **Distance From Mounting Shoulder To Front Face:** 22.6 millimeters **Mounting Facility Thickness:** 0.15 millimeters **Threaded Device Type:** Back shell and coupling facility and mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 17-35 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 135.0 and 170.0 and 200.0 and 310.0 Shell Type: Solid Thread Size: 32.0 millimeters and 25.0 millimeters **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Nickel **Thread Tolerance Class:** 

6g external

**Included Contact Quantity:** 

55 single mating end single contact grouping

## NSN 5935-01-462-7316

Electrical Receptacle Connector - Page 2 of 2



## Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material: Gold Thread Series Designator: Iso m Shelf Life: N/a Unit Of Measure: -Demilitarization: No Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.