

View Online at <https://aerobasegroup.com/nsn/5935-01-463-3752>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

Between 1.730 inches and 1.770 inches

Environmental Protection:

Moisture resistant and vibration resistant

Cable Entrance Diameter:

Between 0.187 inches and 0.227 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Connector Locking Method:

Internally threaded shell

Connector Cable Strain Relief Method:

Shrinkable tubing

End Application:

Rsip ppl

Width Across Flats:

Between 0.245 inches and 0.252 inches

Thready Qty Per Inch (tpi):

36

Thread Size:

0.190 inches

Terminal Location:

Front single mating end single contact grouping

Contact Material:

Beryllium single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment:

Copper alloy single mating end single contact grouping and gold single mating end single contact grouping

Terminal Type:

Wire lead single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Shell Material Specification:

Qq-s-784 federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Plating on inner and outer sleeves and center contact gold

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-f-14072 spec.