

View Online at <https://aerobasegroup.com/nsn/5935-01-465-0202>

Body Style:

Straight shape, internal coupling w/backshell

Overall Length:

1.500 inches

Overall Diameter:

0.510 inches

Environmental Protection:

Moisture resistant and salt water resistant

Cable Entrance Diameter:

0.377 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

2.0 megahertz single mating end single contact grouping

Connector Locking Method:

Lock tab

Connector Cable Strain Relief Method:

Shrinkable tubing

End Application:

1660-00-325-2746

Cable Opening Length:

0.437 inches

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Astm b16 assn standard single material response single mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 single mating end single contact grouping

Precious Material And Location:

Contact gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.