

View Online at <https://aerobasegroup.com/nsn/5935-01-465-1271>

**Body Style:**

Straight shape w/solder mount

**Overall Length:**

1.500 inches

**Overall Diameter:**

0.510 inches

**Cable Entrance Diameter:**

0.337 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:**

2.0 megahertz single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0 and 125.0 and 110.0

**Connector Locking Method:**

Lock tab

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Female terminal connection single mating end single contact grouping

**Contact Material Specification:**

Astm b16 assn standard single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Nickel

**Shell Surface Treatment Specification:**

Mil-p-27418 military specification single treatment response

**Shell Material Specification:**

Astm b16 assn standard single material response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Special Features:**

Material-body and center contact brass; finish-body sulfamate nickel plate, center contact bright gold plate; drawing name connector, electrical, rf

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.