

View Online at <https://aerobasegroup.com/nsn/5935-01-465-1271>

Body Style:

Straight shape w/solder mount

Overall Length:

1.500 inches

Overall Diameter:

0.510 inches

Cable Entrance Diameter:

0.337 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

2.0 megahertz single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 125.0 and 110.0

Connector Locking Method:

Lock tab

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Female terminal connection single mating end single contact grouping

Contact Material Specification:

Astm b16 assn standard single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-p-27418 military specification single treatment response

Shell Material Specification:

Astm b16 assn standard single material response

Included Contact Quantity:

1 single mating end single contact grouping

Special Features:

Material-body and center contact brass; finish-body sulfamate nickel plate, center contact bright gold plate; drawing name connector, electrical, rf

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.