NSN 5935-01-465-3158

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-465-3158

Straight shape
Overall Length:
6.880 inches
Overall Height:
0.545 inches
Overall Width:
0.375 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant
Unthreaded Mounting Hole Diameter:
Between 0.096 inches and 0.101 inches
Distance Between Mounting Facility Centers:
6.550 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Shell Type:
Solid
Features Provided:
Low insertion force contact
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic mineral filled single mating end
Terminal Type:
Printed circuit single mating end single contact grouping
Insert Material Specification:

постанали организации

Mil-m-24519, type gpt-15f military specification single material response single mating end

Included Contact Quantity:

124 single mating end single contact grouping

Included Contact Type:

Brush socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

NSN 5935-01-465-3158

Electrical Receptacle Connector - Page 2 of 2



Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-24519 spec.