## NSN 5935-01-465-4138

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-465-4138 **Body Style:** Straight shape **Overall Length:** Between 2.840 inches and 2.860 inches **Overall Height:** Between 0.460 inches and 0.470 inches Overall Width: Between 0.245 inches and 0.255 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** Between 2.595 inches and 2.605 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys **Connector Locking Method:** Friction **End Application:** F16 aircraft **Terminal Location:** Front single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Terminal Type:** Pin jack single mating end single contact grouping **Guide Design And Location:** D shape socket left-hand at 12 oclock and d shape pin right-hand at 12 oclock **Included Contact Quantity:** 40 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contacts gold **Precious Material:** Gold

N/a

Shelf Life:

## NSN 5935-01-465-4138

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure	Uni	t Of	Meas	ure:
-----------------	-----	------	------	------

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-55302 spec.