## NSN 5935-01-466-2823

**Body Style:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-466-2823

Straight type
Overall Length:
2.650 inches
Overall Height:
0.535 inches
Overall Width:
0.250 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
2.400 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
36 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Folarization Metriou.
Jackscrew
Jackscrew
Jackscrew Shell Type:
Jackscrew Shell Type: Solid
Jackscrew Shell Type: Solid Connector Locking Method:
Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket
Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location:
Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping
Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Terminal Type:
Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Terminal Type: Printed circuit single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Terminal Type: Printed circuit single mating end single contact grouping Unable To Decode:
Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Terminal Type: Printed circuit single mating end single contact grouping Unable To Decode: Unable to decode and unable to decode
Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Terminal Type: Printed circuit single mating end single contact grouping Unable To Decode: Unable to decode and unable to decode Included Contact Quantity:
Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Terminal Type: Printed circuit single mating end single contact grouping Unable To Decode: Unable to decode and unable to decode Included Contact Quantity: 36 single mating end single contact grouping
Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Terminal Type: Printed circuit single mating end single contact grouping Unable To Decode: Unable to decode and unable to decode Included Contact Quantity: 36 single mating end single contact grouping Included Contact Type:
Shell Type: Solid  Connector Locking Method: Jackscrew-socket  Terminal Location: Back single mating end single contact grouping  Terminal Type: Printed circuit single mating end single contact grouping  Unable To Decode: Unable to decode and unable to decode Included Contact Quantity:  36 single mating end single contact grouping  Included Contact Type: Round pin single mating end single contact grouping

81349-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-c-55302/58 government specification

## NSN 5935-01-466-2823

Electrical Receptacle Connector - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0