Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-466-4767

View Online at https://aerobasegroup.com/nsn/5935-01-466-4767
Body Style:
Straight shape
Overall Length:
1.385 inches
Overall Height:
1.170 inches
Overall Width:
4.325 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and corrosion resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.276 inches and 0.286 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.558 inches and 0.566 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 3.871 inches and 3.879 inches
Distance From Mounting Shoulder To Front Face:
Between 0.519 inches and 0.534 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
64 single mating end
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 200.0 degrees celsius
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c cl 1 military specification single treatment response single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings



Shell Material: Aluminum alloy **Shell Surface Treatment:** Nickel **Shell Surface Treatment Specification:** Mil-c-26074, grade a, cl 3 or 4 military specification single treatment response **Shell Material Specification:** Qq-a-591 federal specification single material response **Included Contact Quantity:** 64 single mating end single contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Special Features:** Furnished items - spare contact **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.071 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-c-83733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-c-83733/1 government specification Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.