# NSN 5935-01-466-5980

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-466-5980

# **Body Style:**

Straight shape, external coupling

### **Overall Length:**

0.956 inches

# **Overall Diameter:**

0.234 inches

### **Environmental Protection:**

Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

Nonstd single mating end

### **Contact Maximum Frequency Rating:**

500.0 megahertz single mating end single contact grouping

### Connector Locking Method:

Friction

#### **End Application:**

Ca-117/sys-2a nimitz class cvn

# **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

# **Terminal Location:**

Front single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### Crimping Tool Identifying Number:

00779-69710-2

### **Terminal Type:**

Pin jack single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

#### **Shell Material:**

Copper alloy

### Shell Surface Treatment:

Gold

### Shell Material Specification:

Qq-b-626 federal specification single material response

#### **Included Contact Quantity:**

1 single mating end single contact grouping

#### Included Contact Type:

Coaxial socket single mating end single contact grouping

Electrical Plug Connector - Page 2 of 2



**Precious Material And Location:** 

Contact and shell plating gold

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0