NSN 5935-01-467-3624

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-467-3624

Body Style:

Straight shape, external coupling

Unable To Decode:

Unable to decode and unable to decode

Overall Length:

1.918 inches

Overall Height:

Between 1.969 inches and 2.031 inches

Overall Width:

Between 1.969 inches and 2.031 inches

Environmental Protection:

Weather resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.557 inches and 1.567 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.557 inches and 1.567 inches

Distance From Mounting Shoulder To Front Face:

Between 0.750 inches and 0.781 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

28-15 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Contact

Insert Position In Deg:

110.0

Connector Locking Method:

Externally threaded shell

End Application:

5895-01-384-6751

Terminal Location:

Front single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Rubber chloroprene class cr single mating end

Contact Surface Treatment Specification:

Mil-g-45204 federal specification all treatment responses single mating end single contact grouping

NSN 5935-01-467-3624

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder stud single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
35 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Furnished items - grommet and sealing plug
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.