Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-468-4948

Thread Class:
2a
Thread Direction:
Right-hand
Overall Length:
1.180 inches
Overall Diameter:
1.427 inches
Environmental Protection:
Moisture resistant and salt spray proof and vibration proof
Unthreaded Mounting Hole Diameter:
1.271 inches
Threaded Device Type:
Back shell
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Push-pull
Operating Tempurature Rating:
Between 25.0 degrees celsius and 200.0 degrees celsius
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 military specification all treatment responses
Shell Material Specification:
Qq-a-367 federal specification single material response
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surface gold Precious Material:
Gold
Specification Data:
96906-ms3424 government standard

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

spec.