NSN 5935-01-468-4948

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-468-4948 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Length:** 1.180 inches **Overall Diameter:** 1.427 inches **Environmental Protection:** Moisture resistant and salt spray proof and vibration proof **Unthreaded Mounting Hole Diameter:** 1.271 inches **Threaded Device Type:** Back shell **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Push-pull **Operating Tempurature Rating:** Between 25.0 degrees celsius and 200.0 degrees celsius **Shell Material:** Aluminum alloy 6061 **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416 military specification all treatment responses **Shell Material Specification:** Qq-a-367 federal specification single material response **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surface gold **Precious Material:** Gold **Specification Data:**

96906-ms3424 government standard

NSN 5935-01-468-4948

Electrical Receptacle Connector - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	

Mil-std (military Standard):

Shelf Life:

spec.