NSN 5935-01-469-1683

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-469-1683

Body Style:
Straight shape, external coupling
Overall Length:
33.7 millimeters
Overall Height:
33.3 millimeters
Overall Width:
33.3 millimeters
Center To Center Distance Between Mounting Facilities Parallel To Height:
27.0 millimeters
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
27.0 millimeters
Distance From Mounting Shoulder To Front Face:
19.5 millimeters
Mating End Quantity:
1
Contact Position Arrangement Style:
17-35 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 and 80.0 and 142.0 and 196.0 and 293.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
End Application:
1520-01-135-8250
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Mil-c-39029 military specification all material responses single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Included Contact Quantity:

55 single mating end single contact grouping

NSN 5935-01-469-1683

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Color:
Natural
Supplementary Features:
Mounting method - flange
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-38999 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard): Mil-c-39029 spec.