NSN 5935-01-469-8514

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-469-8514

Body Style:

Straight shape, internal coupling

Overall Length:

1.250 inches

Overall Diameter:

0.593 inches

Environmental Protection:

Vibration resistant and shock resistant and corrosion resistant and moisture resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Frequency Rating:

4.0 gigahertz single mating end single contact grouping

Connector Locking Method:

Shell twistlock

Connector Cable Strain Relief Method:

Crimp type

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

End Application:

1520-01-135-8250

Operating Tempurature Rating:

Between -65.0 degrees celsius and 165.0 degrees celsius

Terminal Location:

Front single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45024 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Qq-n-290 federal specification single treatment response

Included Contact Quantity:

1 single mating end single contact grouping

NSN 5935-01-469-8514

Electrical Plug Connector - Page 2 of 2



			-1-	٠.	<u> </u>		-4	Tvi	
ı	IIC	ıu	ue	u	υU	III	Cι	1 7 1	JE.

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Center terminal finish gold and outer contact finish silver

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45024 spec.