

View Online at <https://aerobasegroup.com/nsn/5935-01-470-0736>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.500 inches

Overall Diameter:

0.690 inches

Environmental Protection:

Vibration resistant and shock resistant and corrosion resistant

Mounting Facility Thickness:

0.109 inches

Threaded Device Type:

Hub

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Insert Position In Deg:

60.0 and 180.0 and 300.0

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Crimp type

End Application:

1520-01-135-8250

Operating Temperature Rating:

Between -65.0 degrees celsius and 165.0 degrees celsius

Thready Qty Per Inch (tpi):

28

Thread Size:

0.500 inches

Terminal Location:

Front single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin jack single mating end single contact grouping

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Qq-n-290 federal specification single treatment response

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Center contact plating gold

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.