

View Online at <https://aerobasegroup.com/nsn/5935-01-470-6575>

Body Style:

Straight shape

Overall Length:

1.100 inches

Cable Entrance Diameter:

0.120 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

350.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

12.4 gigahertz single mating end single contact grouping

Connector Locking Method:

Internally threaded coupling nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

End Application:

1520-01-355-8250 helicopter, attack

Width Across Flats:

0.310 inches

Operating Temperature Rating:

Between -65.0 degrees celsius and 165.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45024 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Steel comp 303

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Special Features:

Drawing name-connector, electrical, rf, coaxial, series sma, weatherproof

Precious Material And Location:

Contact gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45024 spec.