

View Online at <https://aerobasegroup.com/nsn/5935-01-470-8109>

**Body Style:**

Straight shape

**Overall Length:**

Between 2.073 inches and 2.103 inches

**Overall Height:**

0.653 inches

**Overall Width:**

Between 0.479 inches and 0.509 inches

**Environmental Protection:**

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:**

Between 1.847 inches and 1.857 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

44 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

**Contact Surface Treatment Specification:**

Mil0g-45204 , type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Metal

**Shell Surface Treatment:**

Zinc

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification all treatment responses

**Insert Material Specification:**

Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f orty get-30f military specification  
2nd material response single mating end

**Included Contact Quantity:**

44 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.044 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-24308/6 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

spec.