## NSN 5935-01-470-8414

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-470-8414

**Body Style:** 

Straight shape

**Overall Length:** 

Between 1.526 inches and 1.556 inches

**Overall Height:** 

0.663 inches

**Overall Width:** 

Between 0.479 inches and 0.509 inches

**Environmental Protection:** 

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:** 

Between 1.307 inches and 1.317 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

"2, 15" single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Mating end

**Connector Locking Method:** 

Spring friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Surface Treatment:** 

Zinc

**Insert Material Specification:** 

Mil-m-19833, type gdi-30f or mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

15 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

## NSN 5935-01-470-8414

Mil-std (military Standard):

Mil-m-19833 spec.

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-24308/2 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0