Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-470-8433

### **Body Style:**

Straight shape

# **Overall Length:**

Between 2.714 inches and 2.744 inches

# **Overall Height:**

0.663 inches

# **Overall Width:**

Between 0.479 inches and 0.509 inches

### **Environmental Protection:**

Corrosion resistant and moisture proof and shock resistant and vibration resistant

# **Unthreaded Mounting Hole Diameter:**

Between 0.086 inches and 0.091 inches

### Distance Between Mounting Facility Centers:

Between 2.495 inches and 2.505 inches

### Mating End Quantity:

**Contact Position Arrangement Style:** 

37 single mating end

# **Contact Removability:**

Removable single mating end single contact grouping

# **Polarization Method:**

Mating end

### Shell Type:

Solid

1

**Terminal Location:** 

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

# **Terminal Type:**

Wire loop single mating end single contact grouping

# Shell Surface Treatment:

Zinc

# Shell Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

### **Included Contact Quantity:**

37 single mating end single contact grouping

### **Included Contact Type:**

Round socket single mating end single contact grouping



Precious Material And Location:

Contact surface gold

**Precious Material And Weight:** 

0.037 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-24308/6 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0