

View Online at <https://aerobasegroup.com/nsn/5935-01-470-8655>

**Body Style:**

Straight shape

**Overall Length:**

Between 2.620 inches and 2.650 inches

**Overall Height:**

0.595 inches

**Overall Width:**

Between 0.590 inches and 0.620 inches

**Environmental Protection:**

Corrosion resistant and humidity resistant and shock proof and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:**

Between 2.401 inches and 2.411 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

78 single mating end

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end and plastic polyester glass filled single mating end

**Shell Material:**

Metal

**Shell Surface Treatment:**

Zinc

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification all treatment responses

**Insert Material Specification:**

Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military specification  
2nd material response single mating end

**Test Data Document:**

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-24308/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.