NSN 5935-01-471-4032

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-471-4032

View Crimine at https://acrossacogreeqp.ccm/nor/recess CT 17 1 1002
Thread Pitch Diameters:
+25.50/+25.70 millimeters
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Unable To Decode:
Unable to decode and unable to decode
Overall Length:
32.5 millimeters
Overall Diameter:
Between 41.0 millimeters and 46.0 millimeters
Environmental Protection:
Corrosion resistant and weather resistant
Distance From Mounting Shoulder To Front Face:
22.6 millimeters
Mounting Facility Thickness:
0.15 millimeters
Threaded Device Type:
Hub
Mating End Quantity:
1
Contact Position Arrangement Style:
15-19 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key or multiple key
Shell Type:
Solid
Connector Locking Method:
Detent
End Application:
2350-01-436-0005
Thread Length:
1.9 millimeters
Features Provided:
Scoopproof design and self-locking coupling nut and color band engagement indicator
Thread Size:
28.0 millimeters
Thread Pitch In Millimeters:
0.50

NSN 5935-01-471-4032

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Front single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
19 single mating end single contact grouping
Special Features:
Contacts not supplied with this item-order seperatly
Thread Series Designator:
Iso m
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0