Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-473-7433

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling w/backshell |
| Overall Length: |
| 2.125 inches |
| Overall Height: |
| 2.000 inches |
| Overall Width: |
| 2.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 1.562 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.562 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.812 inches |
| Threaded Device Type: |
| Back shell and coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 28-2 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thready Qty Per Inch (tpi): |
| 18 |
| Thread Size: |
| 1.750 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |



Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Silicon single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and nickel

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.