NSN 5935-01-473-8354

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-473-8354 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 2.125 inches **Overall Height:** 2.000 inches **Overall Width:** 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches **Distance From Mounting Shoulder To Front Face:** 0.812 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 28-21 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.750 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-473-8354

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Silicon single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
16-22 socket contacts in lieu of 16-16
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-5015 spec.