## NSN 5935-01-475-8833

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-475-8833

Thread Class:
2a
Thread Pitch Diameters:
+0.2280/+0.2311 inches
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.635 inches
Overall Height:
0.625 inches
Overall Width:
0.260 inches
Environmental Protection:
Moisture resistant and shock resistant and vibration resistant and thermal shock resistant and corrosion resistant
Unthreaded Mounting Hole Diameter:
0.102 inches
Distance Between Mounting Facility Centers:
0.481 inches
Distance From Mounting Shoulder To Front Face:
0.310 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Sma single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Contact Maximum Frequency Rating:
18.0 gigahertz single mating end single contact grouping
Connector Locking Method:
Externally threaded shell
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Operating Tempurature Rating:
Between -65.0 degrees celsius and 125.0 degrees celsius
Features Provided:
Captive contact and emi filter
Thready Qty Per Inch (tpi):

## NSN 5935-01-475-8833

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic fluorocarbon single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Center contact surfaces gold
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0