## NSN 5935-01-476-8318

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-476-8318 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.234 inches **Overall Diameter:** 1.641 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 21-39 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 18.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch Thread Length: 0.219 inches **Thread Size:** 1.188 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:** 

Aluminum alloy

## NSN 5935-01-476-8318

Electrical Plug Connector - Page 2 of 2



Shell	Surface	<b>Treatment:</b>
OHIGH	Juliace	meatinent.

Cadmium and chromate

**Included Contact Quantity:** 

37 single mating end 2nd contact grouping

**Included Contact Type:** 

Round pin single mating end all contact groupings

**Special Features:** 

Shell to shell conductivity shall be one milliohm

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.039 gold grains, troy and 0.039 silver grains, troy

**Precious Material:** 

Gold and silver

## **Test Data Document:**

81349-ms27467t specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 76823-05a107 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Thread Series Designator:**

Unef

**Specification Data:** 

81349-mil-c-38999 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0