

View Online at <https://aerobasegroup.com/nsn/5935-01-476-8422>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.234 inches

**Overall Diameter:**

1.891 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Threaded Device Type:**

Back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

24-24 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

334.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**End Application:**

B-2 bomber

**Thread Length:**

0.219 inches

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.438 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and silver single mating end all contact groupings

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Included Contact Quantity:**

12 single mating end 2nd contact grouping

**Included Contact Type:**

Round pin single mating end all contact groupings

**Special Features:**

Shell to shell conductivity shall be one milliohm

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Thread Series Designator:**

Unef

**Specification Data:**

81349-mil-c-38999 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0