

NSN 5935-01-477-1382 Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-477-1382 **Thread Class:** 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 32.2 millimeters **Overall Diameter:** 41.7 millimeters **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 21-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 18.0 Shell Type: Solid

Connector Locking Method:

Internally threaded coupling ring

End Application:

B-2 bomber

Thread Size:

31.0 millimeters and 1.375 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

NSN 5935-01-477-1382Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Thread Tolerance Class:
6g external
Included Contact Quantity:
79 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Shell to shell conductivity shall be one milliohm
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-d38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 76823-05a108 drawing (this is the
basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification,
standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Iso m and special acme
Specification Data:
81349-mil-c-38999 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0