Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-477-3366

| Thread Class: |
|---|
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, internal coupling w/strain relief |
| Body Length: |
| 2.688 inches |
| Overall Diameter: |
| 1.387 inches |
| Cable Entrance Diameter: |
| Between 0.291 inches and 0.476 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 17-31 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Key or multiple key |
| Insert Position In Deg: |
| 0.0 and 49.0 and 169.0 and 200.0 and 244.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Thread Size: |
| 1.125 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum |
| Shell Surface Treatment: |
| Cadmium |
| Included Contact Quantity: |
| |

31 single mating end single contact grouping

NSN 5935-01-477-3366

Electrical Plug Connector - Page 2 of 2



Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Pin contacts per mil-c-39029/83-508, cable clamp per mil-c-28840/1

Color:

Olive drab

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-28840 spec.