

NSN 5935-01-477-7604 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-477-7604 **Thread Class:** 2b **Thread Direction:** Right-hand

Body Style: Straight shape, flush mount **Overall Length:** 1.326 inches **Overall Height:** Between 3.060 inches and 3.090 inches

Between 1.985 inches and 2.015 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.783 inches

Overall Width:

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Distance From Mounting Shoulder To Front Face:

Between 0.055 inches and 0.065 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

Contact Position Arrangement Style:

Err-090 all mating ends

Contact Removability:

Removable all mating ends all contact groupings

Shell Type:

Solid

Thready Qty Per Inch (tpi):

Thread Size:

0.112 inches

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic diallyl phthalate all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends

NSN 5935-01-477-7604

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-q-45204 military specification single treatment response all mating ends all contact groupings

Terminal Type:

Crimp all mating ends all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses

Shell Material Specification:

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

Insert Material Specification:

Mil-m-14 military specification single material response all mating ends or 1288bx mfr ref single material response all mating ends

Included Contact Type:

Round pin all mating ends all contact groupings

Precious Material And Location:

Contactsurface gold

Precious Material And Weight:

0.158 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-81659 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-81659/71 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.