NSN 5935-01-478-0095

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-478-0095
Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
2.125 inches
Overall Diameter:
1.969 inches
Environmental Protection:
Fuel resistant and humidity resistant and moisture resistant and oil resistant and salt spray proof and shock resistant and solvent resistant
and vibration resistant and weather resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
28-21 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
110.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
End Application:
C-135 air craft
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.750 inches and 1.750 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Crimping Tool Identifying Number:
81349-mil-dtl-22520

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-478-0095Electrical Plug Connector - Page 2 of 2



Shell Material:
Iron alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Included contacts are per m39029/29-212 size is 16
Color:
Olive drab
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns and uns
Specification Data:
96906-ms3456 government standard and 81349-mil-dtl-5015 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Fiig:
A039b0
Mil-std (military Standard):
Mil-dtl-5015 spec.