NSN 5935-01-478-2174

Thread Class:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-478-2174

2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 33.2 millimeters **Overall Diameter:** 48.0 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 24-19 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 49.0 and 169.0 and 200.0 and 244.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **End Application:** B-2 bomber; aircraft cen sec Thready Qty Per Inch (tpi): 10 **Thread Size:** 37.0 millimeters and 1.625 inches **Thread Pitch In Millimeters:** 1.00 **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:**

Terminal Type:

Crimp single mating end single contact grouping

Gold single mating end single contact grouping

NSN 5935-01-478-2174Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Thread Tolerance Class:
6g external
Included Contact Quantity:
19 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Shell to shell conductivity shall be one milliohm
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-d38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 76823-05a108 drawing (this is the
basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification,
standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Iso m and special acme
Specification Data:
81349-mil-c-38999 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0