NSN 5935-01-478-2462

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-478-2462

Thread Class:
2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
31.0 millimeters
Overall Diameter:
29.3 millimeters
Environmental Protection:
Moisture resistant and shock resistant and thermal shock resistant and vibration resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
15-15 single mating end
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
End Application:
B-2 bomber; aircraft cen sec
Thready Qty Per Inch (tpi):
10
Thread Size:
22.0 millimeters and 1.000 inches
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end all contact groupings
Contact Material:

Contact Surface Treatment:

Gold single mating end all contact groupings

Copper alloy single mating end all contact groupings

NSN 5935-01-478-2462Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Thread Tolerance Class:
6g external
Included Contact Quantity:
14 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Special Features:
Shell to shell conductivity shall be one milliohm
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-d38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 76823-05a108 drawing (this is the
basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification,
standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
lso m and special acme
Specification Data:
81349-mil-c-38999 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0