## NSN 5935-01-478-2713



Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-478-2713 **Thread Class:** 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 33.16 millimeters **Overall Diameter:** 32.5 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 15-97 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 68.0 and 178.0 and 204.0 and 247.0 Shell Type: Solid **Connector Locking Method:** 

Internally threaded coupling ring

**End Application:** 

B-2 bomber; aircraft cen sec

Thread Length:

7.11 millimeters

Thready Qty Per Inch (tpi):

10

**Thread Size:** 

22.0 millimeters and 1.000 inches

**Thread Pitch In Millimeters:** 

1.00

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings

## **NSN 5935-01-478-2713**Electrical Plug Connector - Page 2 of 2



Solder well single mating end all contact groupings  Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium Thread Tolerance Class:	
Aluminum alloy  Shell Surface Treatment:  Cadmium  Thread Tolerance Class:	
Shell Surface Treatment: Cadmium Thread Tolerance Class:	
Cadmium Thread Tolerance Class:	
Thread Tolerance Class:	
Sa external	
6g external	
Included Contact Quantity:	
8 single mating end 2nd contact grouping	
Included Contact Type:	
Round socket single mating end all contact groupings	
Special Features:	
Shell to shell conductivity shall be one milliohm	
Precious Material And Location:	
Contact surfaces gold	
Precious Material:	
Gold	
Test Data Document:	
81349-d38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for	rma
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment	ntal
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 76823-05a108 drawing (this	is th
basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification,	
standard or other document that may be referenced in a basic governing drawing)	
Thread Series Designator:	
lso m and special acme	
Specification Data:	
81349-mil-c-38999 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	