

View Online at <https://aerobasegroup.com/nsn/5935-01-478-2792>

Thread Class:

2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

31.0 millimeters

Overall Diameter:

48.0 millimeters

Environmental Protection:

Salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and solvent resistant and thermal shock resistant and vibration resistant

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

25-29 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0 and 49.0 and 169.0 and 200.0 and 310.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

End Application:

B-2 bomber; aircraft cen sec

Thread Length:

7.11 millimeters and 0.280 inches

Thread Size:

37.0 millimeters and 1.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Thread Tolerance Class:

6g internal

Included Contact Quantity:

29 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Shell to shell conductivity shall be one milliohm

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Test Data Document:

81349-d38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 76823-05a108 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Iso m and special acme

Specification Data:

81349-mil-c-38999 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0