

View Online at <https://aerobasegroup.com/nsn/5935-01-478-3291>

Thread Class:

2b

Thread Direction:

Right-hand

Overall Length:

1.660 inches

Overall Diameter:

1.885 inches

End Application:

Self prot sys, helicopter, uh-60a/uh-60d

Cable Opening Diameter:

1.125 inches

Cable Opening Quantity:

1

Size Designation:

24

Mounting Facility Type And Quantity:

1 threaded coupling

Thready Qty Per Inch (tpi):

18

Thread Size:

1.438 inches

Special Features:

Straight backshell, self-locking, shield band termination (rfi/emi), shrink sleeve accommodation. The finish is class "p" cadmium olive drab over electroless nickel (selective plating). For use with mil-c-5015 crimp, mil-c-26482 series 2, mil-c-81703 series 3 and mil-c-83723 series iii connectors.

Material:

Aluminum alloy

Surface Treatment:

Cadmium and nickel

Style Designator:

Straight type

Surface Treatment:

Cadmium and nickel, electroless

Test Data Document:

81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-85049 government specification and 81349-mil-c-85049/82 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A10100

Mil-std (military Standard):

Mil-c-85049 spec.