Electrical Receptacle Connector - Page 1 of 2



resistant

View Online at https://aerobasegroup.com/nsn/5935-01-480-3163

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
0.785 inches
Overall Width:
0.308 inches
Body Height:
0.420 inches
Environmental Protection:
Cold resistant and heat resistant and pressure proof and humidity resistant and salt water
Unthreaded Mounting Hole Diameter:
0.096 inches
Distance Between Mounting Facility Centers:
0.565 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Solid
Connector Locking Method:
Post jacksocket
End Application:
Stv camera system
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Modified termination tail length 0.125 inches
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0