## NSN 5935-01-481-1941

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-481-1941

**Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 1.044 inches **Overall Height:** 1.438 inches **Overall Width:** 1.438 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.128 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** 0.820 inches **Mating End Quantity: Contact Position Arrangement Style:** 24-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 95.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **End Application:** E-nsn isil; test fixture otps; wraparound assembly **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

## NSN 5935-01-481-1941

Electrical Receptacle Connector - Page 2 of 2



| Shell Material:  |
|--|
| Aluminum alloy   |
| Shell Surface Treatment:   |
| Passivate  |
| Included Contact Quantity:   |
| 128 single mating end single contact grouping  |
| Included Contact Type:   |
| Round pin single mating end single contact grouping  |
| Special Features:  |
| Contact designator 25-35   |
| Precious Material And Location:  |
| Contact surfaces gold  |
| Precious Material And Weight:  |
| 0.128 gold grains, troy  |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain            |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                              |
| Specification Data:  |
| 96906-ms27505 government standard  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |
| Mil-std (military Standard):   |
| Mil-dtl-38999 spec.  |
|  |
|  |
|  |