NSN 5935-01-481-1941

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-481-1941

Body Style: Straight shape, external coupling w/backshell **Overall Length:** 1.044 inches **Overall Height:** 1.438 inches **Overall Width:** 1.438 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.128 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** 0.820 inches **Mating End Quantity: Contact Position Arrangement Style:** 24-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 95.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **End Application:** E-nsn isil; test fixture otps; wraparound assembly **Terminal Location:** Back single mating end single contact grouping **Contact Material:**

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-481-1941

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Passivate
Included Contact Quantity:
128 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contact designator 25-35
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.128 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27505 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-dtl-38999 spec.