NSN 5935-01-481-3570

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-481-3570
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
31.0 millimeters
Overall Diameter:
41.7 millimeters
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
21-35 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 and 49.0 and 169.0 and 200.0 and 244.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
End Application:
Dsets bradley a3; test set, electronics
Thready Qty Per Inch (tpi):
10
Thread Size:
31.0 millimeters and 1.375 inches
Thread Pitch In Millimeters:
4.00

1.00

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-481-3570Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Thread Tolerance Class:
6g external
Included Contact Quantity:
79 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Iso m
Specification Data:
81349-mil-c-38999/26 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0