NSN 5935-01-481-3586

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-481-3586 **Thread Class:** 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 31.0 millimeters **Overall Diameter:** 48.0 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 25-4 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 80.0 and 142.0 and 196.0 and 293.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **End Application:** Dsets bradley a3; test set electronics Thready Qty Per Inch (tpi): 10

Thread Size:

37.0 millimeters and 1.625 inches

Thread Pitch In Millimeters:

1.00

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic epoxy single mating end

NSN 5935-01-481-3586Electrical Plug Connector - Page 2 of 2



Terminal Type:	
Crimp single mating end all contact groupings	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Nickel	
Thread Tolerance Class:	
6g external	
Included Contact Quantity:	
8 single mating end 1st contact grouping	
Included Contact Type:	
Round pin single mating end all contact groupings	
Precious Material And Location:	
Contact surfaces gold	
Precious Material:	
Gold	
Test Data Document:	
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that refle	ect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, refle	ecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "a	verage", "", etc.).
Thread Series Designator:	
lso m and special acme	
Specification Data:	
81349-mil-dtl-38999/26 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-c-38999 spec.	