

View Online at <https://aerobasegroup.com/nsn/5935-01-482-8776>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Angle shape

Unable To Decode:

Unable to decode and unable to decode and unable to decode

Environmental Protection:

Hermetic

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Rf single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Compression nut

Distance From Centerline To Connector End:

1.030 inches

Distance From Centerline To Cable End:

0.630 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.750 inches

Contact Material:

Beryllium single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Special Features:

Washer is a internal toothed lockwasher - connector is a push-on (c) type

Precious Material And Location:

Plating on all metal parts silver

Precious Material:

Silver

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0