

View Online at <https://aerobasegroup.com/nsn/5935-01-482-8776>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape

**Unable To Decode:**

Unable to decode and unable to decode and unable to decode

**Environmental Protection:**

Hermetic

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Rf single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Connector Locking Method:**

Friction

**Connector Cable Strain Relief Method:**

Compression nut

**Distance From Centerline To Connector End:**

1.030 inches

**Distance From Centerline To Cable End:**

0.630 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.750 inches

**Contact Material:**

Beryllium single mating end single contact grouping and copper single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Special Features:**

Washer is a internal toothed lockwasher - connector is a push-on (c) type

**Precious Material And Location:**

Plating on all metal parts silver

**Precious Material:**

Silver

**Thread Series Designator:**

Un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0