Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-483-1580

|      | read Class:                                |
|------|--|
| 2b   |  |
| Th   | read Direction:                            |
| Rig  | ht-hand                                    |
| Ov   | erall Width:                               |
| 1.2  | 10 inches                                  |
| Во   | dy Angle In Deg:                           |
| 90.  | 0  |
| En   | d Application:                             |
| Uh   | -60 helicopter                             |
| Ca   | ble Opening Diameter:                      |
| 0.5  | 00 inches                                  |
| Ca   | ble Opening Quantity:                      |
| 1    |  |
| Siz  | e Designation:                             |
| 16   |  |
| Мо   | unting Facility Type And Quantity:         |
| 1 tł | nreaded coupling                           |
| Th   | ready Qty Per Inch (tpi):                  |
| 20   |  |
| Th   | read Size:                                 |
| 1.0  | 00 inches                                  |
| Sp   | ecial Features:                            |
| 100  | 00 hour corrosion resistant                |
| Ма   | terial:                                    |
| Alu  | minum alloy                                |
| Su   | rface Treatment:                           |
| Ca   | dmium and chromate and nickel              |
| Sty  | /le Designator:                            |
| An   | gle type                                   |
| Su   | rface Treatment:                           |
| Ca   | dmium and chromate and nickel, electroless |
| Th   | read Series Designator:                    |
| Un   | ef   |
| Sh   | elf Life:                                  |
| N/a  | à  |
| Un   | it Of Measure:                             |
|      |  |
| De   | militarization:                            |
| No   |  |
| Fii  | g:   |
| A 1  | 0100                                       |